

Appl. No. 10/707,279
Amdt. dated July 8, 2005
Reply to Office action of May 03, 2005

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

- 1 (currently amended): An adjusting ~~An adjusting~~ apparatus for a projection lamp,
5 comprising:
a base which has two adjusting devices on side surfaces and has a container with at
least one guide-groove on the bottom;
an adjusting module which is placed inside said container, one end of said adjusting
device pressing to a surface of said adjusting module which comprises two
10 adjusting plates, guide-grooves and guide-pins being formed upon said
adjusting plate, one adjusting plate placing said guide-pins in accordance with
said guide-grooves of said base, the other adjusting plate connecting to a lamp;
and
a cover which is ~~place~~ placed on a top surface of said container;
15 wherein said adjusting devices are moved parallel to the length direction of said
guide-grooves.
- 2 (cancelled).
- 20 3 (currently amended): The adjusting apparatus for a projection lamp according to claim 1,
wherein said cover has a window, the dimensions of said window being smaller than
the dimensions of said adjusting plate.
- 25 4 (original): The adjusting apparatus for a projection lamp according to claim 1, wherein
said guide-grooves have repositioning devices inside, two ends of said repositioning
device respectively pressing to said guide-pin and to a surface of said guide groove.

Appl. No. 10/707,279
Amdt. dated July 8, 2005
Reply to Office action of May 03, 2005

5 (currently amended): The adjusting apparatus for a projection lamp according to claim 4,
wherein said repositioning devices ~~could be~~ are springs.

6 (currently amended): An adjusting ~~An adjusting~~ apparatus for a projection lamp,
5 comprising:
a base which has at least one adjusting device on a side surface and has a container
with at least one guide-groove on the bottom;
an adjusting module placed inside said container, which comprises two adjusting
plates, guide-grooves and guide-pins being formed upon said adjusting plate,
10 one adjusting plate placing said guide-pins in accordance with said
guide-grooves of said base, the other adjusting plate connecting to a lamp; and
a cover which is ~~place~~ placed on a top surface of said container;
wherein said adjusting devices are moved parallel to the length direction of said
guide-grooves.

15

7 (cancelled).

8 (currently amended): The adjusting apparatus for a projection lamp according to claim 6,
wherein said cover has a window, the dimensions of said window being smaller than
20 the dimensions of said adjusting plate.

9 (currently amended): The adjusting apparatus for a projection lamp according to claim 6,
wherein one end of said adjusting ~~devices are~~ device is pressed to said adjusting
plate, on side surfaces of said base having at least one repositioning device in
25 accordance with the position of said adjusting ~~devices~~ device, one end of said
repositioning device being fixed to side surface of said base, and the other end
pressing to side surface of said adjusting plate.

Appl. No. 10/707,279
Amdt. dated July 8, 2005
Reply to Office action of May 03, 2005

- 10 (currently amended): The adjusting apparatus for a projection lamp according to claim
9, wherein said repositioning ~~devices could be springs~~ device is a spring.
- 5 11 (currently amended): The adjusting apparatus for a projection lamp according to claim
9, wherein said repositioning ~~devices could be~~ device is an elastic elements element.
- 12 (currently amended): An adjusting ~~An adjusting~~ apparatus for a projection lamp,
comprising:
a base which has at least one adjusting device on a side surface and has a container
10 with at least one guide-groove on the bottom;
an adjusting module placed inside said container, which comprises a fixing plate and
two adjusting plates, one end of said adjusting device pressing to a side surface
of said adjusting plate, adjacent surfaces of said fixing ~~plates~~ plate having
slide-grooves and connecting to a lamp, said adjusting plate placed device
15 ~~placing~~ inside said slide-groove, ~~said adjusting plate and~~ placing guide-pins in
accordance with said guide-grooves; and
a cover which is ~~place~~ placed on a top surface of said container.
- 13 (original): The adjusting apparatus for a projection lamp according to claim 12,
20 wherein said adjusting devices are moved parallel to the length direction of said
guide-grooves.
- 14 (currently amended): The adjusting apparatus for a projection lamp according to claim
12, wherein said cover has a window, the dimensions of said window being smaller
25 than the dimensions of said adjusting plate.
- 15 (currently amended): The adjusting apparatus for a projection lamp according to claim
12, wherein on side surfaces of said base have at least one repositioning device in

Appl. No. 10/707,279
Amdt. dated July 8, 2005
Reply to Office action of May 03, 2005

accordance with the position of said adjusting ~~devices~~ device, one end of said repositioning device being fixed to side surface of said base and the other end pressing to side surface of said fixing plate.

5 16 (currently amended): The adjusting apparatus for a projection lamp according to claim 15, wherein said repositioning ~~devices could be springs~~ device is a spring.

10 17 (currently amended): The adjusting apparatus for a projection lamp according to claim 15, wherein said repositioning ~~devices could be~~ device is an elastic elements element.

18 (currently amended): The adjusting apparatus for a projection lamp according to claim 15, wherein said repositioning ~~devices could be~~ device is a plastic devices device.

15 19 (currently amended): The adjusting apparatus for a projection lamp according to claim 15, wherein said repositioning ~~devices could be~~ device is an elastic deformation frames frame of said base.

20 20 (new): An adjusting apparatus for a projection lamp, comprising:
a base which has two adjusting devices on side surfaces and has a container with at least one guide-groove on the bottom;
an adjusting module which is placed inside said container, one end of said adjusting device pressing to a surface of said adjusting module which comprises two adjusting plates, guide-grooves and guide-pins being formed upon said
25 adjusting plate, one adjusting plate placing said guide-pins in accordance with said guide-grooves of said base, the other adjusting plate connecting to a lamp;
and
a cover which is placed on a top surface of said container;

Appl. No. 10/707,279
Amdt. dated July 8, 2005
Reply to Office action of May 03, 2005

wherein said guide-grooves have repositioning devices inside, two ends of said repositioning device respectively pressing to said guide-pin and to a surface of said guide groove.

- 5 21 (new): An adjusting apparatus for a projection lamp, comprising:
a base which has at least one adjusting device on a side surface and has a container with at least one guide-groove on the bottom;
an adjusting module placed inside said container, which comprises two adjusting plates, guide-grooves and guide-pins being formed upon said adjusting plate,
10 one adjusting plate placing said guide-pins in accordance with said guide-grooves of said base, the other adjusting plate connecting to a lamp, wherein one end of said adjusting device is pressed to said adjusting plate, on side surfaces of said base having at least one repositioning device in accordance with the position of said adjusting device, one end of said repositioning device
15 being fixed to side surface of said base, and the other end pressing to side surface of said adjusting plate; and
a cover which is placed on a top surface of said container.